

Link do produktu: <https://connectivity.pl/3ghdsd-sdi-dvb-asi-madi-fiber-optic-dual-transport-transmitter-p-26.html>



3G/HD/SD-SDI / DVB / ASI / MADI Fiber Optic Dual Transport Transmitter

Cena brutto	4 370,70 zł
-------------	--------------------

Cena netto	3 553,41 zł
------------	--------------------

Kod producenta	BBG-2EO
----------------	----------------

Producent	Cobalt Digital
-----------	-----------------------

Opis produktu

Dual Coax-To-Fiber throw-down converter unit is a new part of the Blue Box group of compact, rugged, and portable converter boxes. Super-easy to use, Blue Box Dual Coax-To-Fiber supports SMPTE 424M, 292M, and 259M as well as DVB, ASI, and MADI audio on two independent coax-to-fiber paths. Auto-mode EQ/reclocking automatically sets to the signal type being received (unrecognized formats are safely passed without reclocking). Its wide operating range (from 5Mbps to 3Gbps) flexibly supports most professional digital serial communications. Fully error-free pathological pattern operation is fully compatible with professional fiber video interfaces.

- Dual independent fiber-to-coax paths – all in one easy to use throw-down box
- Full support of 5Mbps thru 3Gbps transport conversions, with seamless auto-mode EQ/reclocking. No switches to set for different payloads.
- Dual-channel status indicators for data rate and lock
- Compatible with SMPTE 424M, 292M, 259M, 310M, M2S, DVB-ASI, and MADI audio
- Error-free pathological support. Full compatibility with other BlueBox™ Coax/Fiber units and Cobalt 9400-series openGear® frame-installed fiber cards.
- Small rugged portable standalone package ideal for portable installations
- Singlemode fiber link distance >10 km (3Gbps), >20 km (1.5Gbps), and >35 km (270Mbps). Multimode typically > 200 m.
- Available with ST, LC, or FC fiber termination
- Powers from 5 to 16 VDC (AC adapter included). Directly compatible with low-voltage (+12 VDC) automotive/truck systems
- **Power**
5 to 16 VDC,
- **Standards/Data Rates Supported**
SMPTE 424M, 292M, 259M, 344M, 305M, DVB-ASI
5Mbps to 3Gbps pathological pattern operation
(does not support AES-3id audio or other standards using data rates)
- **Input**
(2) 75Ω BNCs. Reclocking automatically engaged for recognized signal standards; bypassed for unrecognized standards.
Return Loss: >18 dBm up to 270 MHz

- **Output**

(2) Fiber outputs. FC, ST, or LC connectors per ordered configuration (see Ordering Info)

Wavelength: 1310 nm

Power: -7.5 dBm (min)

- **Dimensions**

5.0" x 2.9" x 1.1" (including connector projections)

(127 x 74 x 28 mm)